

SPECIFICATION

TITLE OF THE INVENTION

METHOD FOR ASSEMBLING INTEGRAL TYPE ELECTRONIC
COMPONENT AND INTEGRAL TYPE ELECTRONIC COMPONENT

5

BACKGROUND OF THE INVENTION

The present invention relates to a method for
assembling an integral type electronic component which is
manufactured by combining a plurality of electronic
components in one body, and an integral type electronic
component assembled by the method.

In response to the recent advancement of making
electronic components small and light-weight, there has
been proposed a large number of ways to further miniaturize
the electronic components. Many of the electronic
components manufactured by the proposed ways are formed by
combining an electronic component having two or more
functions with a device having one function.

Various mounting processes and facilities have
been developed hitherto to arrange the electronic
components highly accurately with high reliability. A
conventional method of assembling the electronic components
will be described below with reference to Figs. 8-11.

In the first place, conductive adhesive 2 are
supplied onto a board 1 as shown in Fig. 8. Then

electronic components 3 are placed to parts of the
conductive adhesive 2 as shown in Fig. 9 and fixed to the
conductive adhesive 2 with hardening the conductive
adhesive 2. After conductive adhesive 4 are supplied onto
5 the electronic components 3 as shown in Fig. 10, a board 5
is placed on the conductive adhesive 4 as shown in Fig. 11.
The conductive adhesive 4 are hardened last, whereby an
integral type electronic component 6 is formed.

In the conventional arrangement of the above-
10 described manner, the method requires mounting each of the
components onto the board 1 and therefore is not fit for
devices requiring a mounting accuracy, for example, in
mounting optical components necessitating an optical path
alignment, etc. The electronic components 3 undesirably
15 vary in height from the board 1 because the electronic
components 3 are placed on the conductive adhesive 2. As a
result, when the board 5 is mounted onto the electronic
components 3 in the next process, the so-called open fault
that the electronic components 3 and the board 5 are not
20 electrically connected with each other possibly arises.
Further in the case where there are many electronic
components 3 to be mounted, it takes a long time before all
the components 3 are mounted completely, and also there are
problems that a quality of mounting the components on the
25 conductive adhesive 2 deteriorates and a cost increases

because of a long manufacturing time.

SUMMARY OF THE INVENTION

The present invention is devised to solve the above problems and has for its object to provide an easy,
5 high-quality and low-cost method for assembling integral type electronic component and an integral type electronic component assembled by the method.

In order to accomplish the above and other aspects, there is provided a method for assembling an
10 integral type electronic component according to a first aspect of the present invention, which comprises:

storing and holding an electronic component to a component storage part of a first board; and

electrically connecting a second board to the
15 electronic component held to the first board, thereby forming the integral type electronic component of the first board and the second board.

Bumps of the second board may be flattened before the second board is electrically connected to the
20 electronic component after the electronic component is held to the first board.

An integral type electronic component is provided according to a second aspect of the present invention, which comprises:

25 a first board with a component storage part for

storing and holding an electronic component; and

a second board which is electrically connected to the electronic component held to the first board, thereby being united with the first board.

5 In the second aspect, when the electronic component is a light-emitting element, the component storage part may be formed to have a side wall for shielding light of the light-emitting element.

10 In the second aspect, the first board can be formed of any one of glass, ceramic and an organic resin.

In the second aspect, the electronic component may be held to the component storage part with a photo-curing type insulating resin.

15 According to the assembling method for the integral type electronic component of the first aspect of the present invention and the integral type electronic component of the second aspect, the second board is electrically connected to the electronic components after the electronic components are stored and held to the component storage parts of the first board. Therefore, the arrangement accuracy of the electronic components is determined on the basis of the arrangement accuracy of the component storage parts formed to the first board. Also, the electronic components stored in the component storage parts are restricted in motion. Furthermore, since it is

20

25

enough simple to insert the electronic components to the component storage parts, a long time is not required to finish the mounting as compared with the conventional art even if a lot of electronic components are to be mounted.

5 The manufacturing time is shortened and costs can be reduced in comparison with the conventional art.

The electronic components can be arranged highly accurately and simply at low costs in comparison with the conventional art.

10 The so-called open fault can be avoided by flattening the bumps of the second board.

BRIEF DESCRIPTION OF THE DRAWINGS

15 These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying drawings, in which:

20 Fig. 1 is a sectional view of a first board among diagrams showing each of states of board and the like which is obtained by carrying out a method for assembling integral type electronic component according to an embodiment of the present invention;

25 Fig. 2 is a sectional view of the first board indicating a state with electronic components filled in

component storage parts of the first board shown in Fig. 1;

Fig. 3 is a sectional view of the first board indicating a state in which electronic components filled in the first board of Fig. 1 are fixed with an adhesive;

5 Fig. 4 is a side view of a second board to be fitted to the first board of Fig. 1;

Fig. 5 is a diagram showing a state in which the first board of Fig. 3 and the second board of Fig. 4 are joined;

10 Fig. 6 is a diagram of a state in which a third board is joined to the board obtained by joining the first board and the second board;

Fig. 7 is a flow chart explanatory of the method for assembling integral type electronic component in the embodiment of the present invention;

15 Fig. 8 is a diagram showing a state with a conductive adhesive supplied to a board among diagrams showing each of states of board and the like which is obtained by carrying out a conventional method for assembling integral type electronic component;

20 Fig. 9 is a diagram of a state with components mounted to the conductive adhesive of Fig. 8;

Fig. 10 is a diagram of a state with a conductive adhesive supplied to upper parts of components of Fig. 9;

25 and

Fig. 11 is a diagram of a state with a board mounted to an upper part of the conductive adhesive of Fig. 10.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A method for assembling integral type electronic component, and an integral type electronic component assembled by the integral type electronic component assembling method which are embodiments of the present invention will be described below with reference to the drawings. Before the description of the present invention proceeds, it is to be noted that like parts are designated by like reference numerals.

The integral type electronic component assembling method is carried out in a manner as will be discussed below.

In a step (designated by "S" in Fig. 7) 1 of Fig. 7, component storage parts 102 are formed by dry etching or wet etching to a first board 101 as shown in Fig. 1. Each of the component storage parts 102 is a recessed part in which an electronic component 103 to be described below can be stored. Each component storage part may be a bottomed shape or can be, e.g., a through hole penetrating in a thickness direction of the first board 101 as indicated in Fig. 1. Although a plurality of the component storage

parts 102 are formed to the first board 101 in Fig. 1, there may be formed one storage part from a relationship with the electronic component 103 to be stored. The component storage part 102 is necessary to be larger by, for instance, 5-30 μ m than the electronic component 103 to be stored. For example, an Si substrate, a glass substrate, a ceramic substrate, an organic resin material substrate or the like is used as the first board 101.

A crystal orientation of Si may be any of (1,1,1), (1,0,0) and (1,1,0) when the Si substrate is used.

In a next step 2, as shown in Fig. 2, the electronic components 103 are disposed to the component storage parts 102. The electronic component 103 corresponds to, for example, a light-emitting element such as an LED (light-emitting diode) or the like, an IC of Si substrate, an IC of GaAs substrate, a resistor, a capacitor or the like. For the electronic component 103 being, e.g., the LED, an orientation of the LED is controlled by a mounting machine having a recognition function, so that the LED is stored in the component storage part 102 with a light-emitting part of the LED directed down in the drawing. Although the electronic components 103 are placed to all of the component storage parts 102 in Fig. 2, the present embodiment is not limited to this arrangement and the electronic component(s) 103 is sometimes placed to only

part of the component storage parts 102 in relation to a circuit design.

When the electronic component 103 is a light-emitting element such as an LED or the like, the component storage part 102 may be formed to have a side wall 1012 for shielding light of the light-emitting element. The side wall 1012 can prevent, for example, interference due to light emitted from an adjoining LED from arising.

In a succeeding step 3, as in Fig. 3, an insulating adhesive 104 is filled and then cured in the component storage part 102 with the electronic component 103 stored therein. An adhesive of a type cured with ultraviolet rays, a thermosetting type adhesive or the like can be used as an example of the insulating adhesive 104. When the adhesive to be cured with ultraviolet rays is used, for instance, the adhesive is cured by applying ultraviolet rays after the adhesive is filled.

In a next step 4, gold bumps 106 are formed correspondingly to the electronic components 103 to a second board 105 which is to be electrically connected to the electronic components 103. In a next step 5, it is decided whether or not leading end parts of the gold bumps 106 of the second board 105 are to be flattened. When the flattening is determined to be necessary, the step goes to a next step 6 and the flattening is carried out. Then the

step moves to a next step 7. On the other hand, when the flattening is determined to be unnecessary, the step skips to the step 7. Whether the flattening is necessary or not may be judged by a worker.

5 In the step 7 as shown in Fig. 4, a conductive adhesive 107 is applied to the leading end parts of the gold bumps 106 of the second board 105. The second board 105 may be a semiconductor chip of, e.g., Si, GaAs, InP or the like. In the step 7, the first board 101 with the
10 electronic components 103 and the second board 105 with the gold bumps 106 are aligned to make the electronic components 103 and the gold bumps 106 meet each other, as indicated in Fig. 5. Then the first board 101 and the second board 105 are fitted. After the fitting, the
15 conductive adhesive 107 is cured thereby joining the first board 101 and the second board 105. A first integral type electronic component 110 is formed in this manner.

 According to the present embodiment, further in a step 8, a third board 108 is joined with a conductive
20 adhesive 109 to the above-joined first board 101 and second board 105. A second integral type electronic component 111 may be formed accordingly as shown in Fig. 6.

 The assembling method for the integral type electronic component, and the integral type electronic
25 component assembled by the method can exert the following

effects. It has conventionally been the problem in the circumstances without the first board 101 how to assemble small components while fixedly transferring the components. That is, a process related to the arranging and fixing the components has been complicated in the conventional art, thereby raising problems of a yield decrease, etc. In contrast to this, according to the present embodiment, an arrangement accuracy of electronic components 103 is determined on the basis of an arrangement accuracy of component storage parts 102 formed to the first board 101. Moreover, the electronic components 103 stored in the component storage parts 102 are limited in motion. In order to arrange the electronic components 103, it is enough only to insert the electronic components 103 to the component storage parts 102. The arrangement is thus made simple. It won't take a long time before an end of the mounting as compared with the conventional art even if there is a large number of electronic components 103 to be mounted. The manufacturing time is shortened and costs can be reduced in comparison with the conventional art.

The arrangement of the electronic components 103 is realized highly accurately and simply at low costs in comparison with the conventional art.

Additionally, the open fault is prevented because the bumps 106 of the second board 105 are flattened.

5